



Waterproof connection for RS-232C & power adaptor



Waterproof (IP67) indicator



Bright coparator lights for checkweighing

CK200SC SERIES

Static Checkweighing

Waterproof Bench Scale

Fully stainless steel construction, suitable for use in moist industrial environments such as food processing and chemical plants.


- **Trade Approved (NMI No. 6/4C/285)**
Dual Interval (Non-Trade), Single Interval (Trade)
- Stainless steel base & loadcell
- Waterproof indicator (IP67)
- Waterproof connector for RS-232C & power cable
- Checkweighing function with bright coparator lights and buzzer
- High-visibility LED display
- Various power supply: 12VDC adaptor / 6V Pb rechargeable battery



CK200SC SERIES | Static Checkweigher Bench Scale

Waterproof Cable Connection

Waterproof power and cables allow the CK200SC to be safely used in wet environments. CK200SC can be moved freely with its convenient cable connector.



Stainless Steel Construction

Full stainless steel construction of the base offers protection against corrosion and is easy to clean. Combined with a stainless steel load cell and indicator (IP67), the CK200SC is ideal for wet environments.



Various Power Supply

The CK200SC can be operated with both an DC adaptor or a rechargeable battery allowing the scale to be used in environments where an external power source is not available.



Checkweighing Comparator Lights

3 different coloured lights indicate the comparison results of UNDER (yellow), OK (green) and OVER (red) for a fast and effective checkweighing result verification.



Specifications

Technical Data

Model	CK200SC				
Max. Capacity (kg)	6	15	30	60	150
Division (g)	2	5	10	20	50
External Resolution	1/3,000				
Display	6 digit LED/ LED colour bar (weight comparison)				
Display Signals	Stable, Zero, Tare, G/N, BAT, Hold, COM, kg, lb, UNDER/OK/OVER				
Key Pad	10 Numeric & 5 Function keys				
Power	DC 12V 1.5A Adaptor / 6V 5A Pb Rechargeable battery				
Battery Life	Approx. 30hrs (charging 12hrs)				
Operating Temp.	-10°C ~ 40°C				
Interface	RS-232C (Standard) / RS-422/RS-485 (Optional)				
Platform Size (mm)	280 x 280		400 x 520		
Product Size (mm)	293 x 336 x 510		400 x 610 x 778		
Product Weight (kg)	8.8		20.5		

FEATURES

- Stainless Steel Construction
- Stainless Steel Load Cell & IP67 Indicator
- LED Display
- Numeric & function keys
- RS-232C interface (RS-422/RS-485 Optional)
- Bright comparator lights for checkweighing
- External resolution 1/3,000
- Full digital calibration
- Weight backup functions
- Multiple weights setup function
- Command mode function
- Tare input functions using keys
- Gravity calibration functions
- Adjustable display for easy viewing
- Waterproof cable connection

CAS

UNIT 8, NORTHLINK, 459 TUFNELL ROAD
BANYO QLD 4014, AUSTRALIA

TEL: +61 (0)7 3267 7767 FAX: +61 (0)7 32 67 1818

EMAIL: sales@cassscale.com.au

<http://www.cassscale.com.au>

Specifications are subject to change for improvement without prior notice.